



SRK50ZS-W

5.0kW

Specifications

Nominal cooling capacity		kW	5.0
Nominal heating capacity		kW	5.8
Sound power level	Cooling	dB(A)	59
	Heating	dB(A)	60
Sound pressure level	Cooling(Hi/Me/Low/Ulo)	dB(A)	46 / 36 / 29 / 22
	Heating(Hi/Me/Low/Ulo)	dB(A)	46 / 37 / 31 / 24
Air flow	Cooling(Hi/Me/Low/Ulo)	m ³ /min	12.1 / 9.9 / 7.4 / 5.9
	Heating(Hi/Me/Low/Ulo)	m ³ /min	13.9 / 11.2 / 9.1 / 7.4
Exterior dimensions (H×W×D)		mm	290×870×230
Net weight		kg	10.0
Refrigerant piping size	Liquid / Gas	mm (ø inch)	6.35(1/4") / 12.7(1/2")
Clean filter			Allergen Clear Filter × 1, Photocatalytic Washable Deodorizing Filter × 1

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics

